



UNITY DUAL 6 X 2.4 kW

The All In One Solution.

Today's entertainment productions require more and more data on set as smart lights are evolving rapidly with higher channel counts and more universes of DMX being required. RatPac's Unity stands alone as an all-in-one solution as a dimmer (at 1.2k or 2.4k), switchable power source, opto-splitter and unmanaged switch. 11 universes of DMX output in all.



UNITY EDISON DUAL 6x2.4 kW

INPUT: 100A 120V 60HZ SINGLE PHASE INPUT POWER WITH BATES STAGE PIN CONNECTOR
OUTPUT: 6X2.4 kW OUTPUT CHANNELS

OVERLOAD PROTECTION
20A RESETTABLE BREAKERS

CONTROL

ALL FEATURES CONFIGURABLE VIA USER INTERFACE DISPLAY SCREEN OR WEB GUI
INTERNAL RECHARGEABLE BATTERY ALLOWS CONFIGURATION WITHOUT POWER
4 WAY ROTARY SWITCH CAN QUICKLY CHANGE MODES FOR CHANNELS GLOBALLY OR INDIVIDUALLY.
USB FIRMWARE UPDATE VIA USB PORT

FEATURES

ETHERNET ENABLED, COMPATIBLE WITH ART-NET OR sACN 9 PORT INTEGRATED GIGABIT ETHERNET SWITCH

ETHERNET STATUS & SPEED LED INDICATORS PER ETHERNET PORT

8 UNIVERSE DMX NODE, WITH 8 INDIVIDUALLY CONFIGURABLE XLR OUTPUT PORTS WITH SEPARATE UNIVERSES AND CAPABILITY:
12 XLR PORTS IN ALL PLUS DMX PASS THROUGH 2 UNIVERSES OF CRMX WIRELESS, TX OR RX
SELF-TERMINATING DMX WITH STATUS QUO FOR ALL XLR OUTPUTS

GHOST LOAD FEATURE FOR PROBLEMATIC FIXTURES SUCH AS DIMMABLE LEDS AND LOW WATTAGE INCANDESCENTS SELECTABLE

DIMENSION

17"W X 10.75"H X 10.5"D
WEIGHT: 33 LBS

MODEL

531.0011.001.0A



[CLICK FOR VIDEO INSTRUCTION](#)

TECH SUPPORT



"QUIET ON SET."