



UNITY U-GROUND 12X1.2kW/6 X 2.4kW CANADA

The All In One Solution.

Today's entertainment productions require more and more data on set as smart lights are evolving rapidly with higher channel counts and more universes of DMX being required. RatPac's Unity stands alone as an all-in-one solution as a dimmer (at 1.2k or 2.4k), switchable power source, opto-splitter and unmanaged switch. 11 universes of DMX output in all: 2 Universes of wireless DMX and 8 in the node (except in sACN Multicast, which is 7) plus one universe through the ethernet patch.



UNITY U-GROUND 12X1.2 kW/6x2.4kW CANADA

INPUT: 100A 120V 60HZ SINGLE PHASE
E1018 CAMLOCK
OUTPUT: 12 CHANNELS AT 1.2kW OR
6 CHANNELS AT 2.4 kW

OVERLOAD PROTECTION

20A RESETTABLE BREAKERS

CONTROL

ALL FEATURES CONFIGURABLE VIA USER
INTERFACE DISPLAY SCREEN OR WEB GUI
INTERNAL RECHARGEABLE BATTERY ALLOWS
CONFIGURATION WITHOUT POWER
4 WAY ROTARY SWITCH CAN QUICKLY
CHANGE MODES FOR CHANNELS GLOBALLY
OR CHANNELS CAN BE INDIVIDUALLY
CONFIGURED THROUGH THE GUI OR CONSOLE.
USB FIRMWARE UPDATE VIA USB PORT
USING A PC

FEATURES

ETHERNET ENABLED, COMPATIBLE WITH
ART-NET OR sACN.
9 PORT INTEGRATED UNMANAGED GIGABIT
ETHERNET SWITCH
ETHERNET STATUS & SPEED LED INDICATORS
PER ETHERNET PORT
8 UNIVERSE DMX NODE, WITH 8 INDIVIDUALLY
CONFIGURABLE XLR OUTPUT PORTS WITH
SEPARATE UNIVERSES AND CAPABILITY:
8 UNIQUE UNIVERSES AVAILABLE IN ARTNET
OR 7 IN sACN MULTICAST
FOUR PORT OPTOSPLITTERS CONTROLLED BY
PORT E
12 XLR PORTS IN ALL PLUS DMX PASS THROUGH
2 UNIVERSES OF CRMX WIRELESS, TX OR RX
SELF-TERMINATING DMX WITH STATUS QUO
FOR ALL XLR OUTPUTS

GHOST LOAD

SELECTABLE GHOST LOAD FEATURE FOR
PROBLEMATIC FIXTURES SUCH AS DIMMABLE
LEDS AND LOW WATTAGE INCANDESCENTS

DIMENSIONS

17"W X 10.75"H X 11"D
WEIGHT: 35 LBS

MODEL

531.0261.001.0A



[CLICK FOR VIDEO
INSTRUCTION](#)

TECH SUPPORT



"QUIET ON SET."